

AMENDMENTS TO THE CLAIMSLISTING OF CLAIMS

This listing of claims will replace all prior versions, and listings, of the claims in the application.

Claim 1. (Currently Amended) An information signal transmission method of transmitting a primary information signal from a first electronic device to a second electronic device acting as a sender in a system via a transmission line connected between an analog output terminal of said first electronic device acting as a receiver in the system and an analog input terminal of said second electronic device, said method being characterized in that:

said second electronic device supplies, in the form of an electronic signal, device information associated with said second electronic device over said information signal transmission line; and

said first electronic device detects said device information supplied in the form of the electronic signal over said transmission line and controls outputting of said primary information signal to said second electronic device in accordance with the detected device information, wherein

said second electronic device is a recording device for recording said primary information signal on a recording medium which, when it has come into a recording mode in which said primary information signal is to be recorded on said recording medium,

supplies over said transmission line operation status information indicating said recording device is in said recording mode, and said first electronic device detects said operation status information received via said transmission line and controls outputting of said primary information signal in accordance with a status indicated by said detected operation status information.

Claim 2. (Previously Presented) The information signal transmission method according to Claim 1, wherein when said second electronic device detects that an electronic device is brought into connection with said second electronic device via said analog input terminal, said second electronic device supplies said device information over said transmission line.

Claim 3. (Previously Presented) The information signal transmission method according to Claim 1, wherein when said first electronic device detects that an electronic device is brought into connection with said first electronic device via said analog output terminal, said first electronic device detects said device information supplied via said transmission line.

Claim 4. (Previously Presented) The information signal transmission method according to Claim 1, wherein said first electronic device controls outputting of said primary information signal so that said primary information signal is output after detecting said device information supplied via said transmission

line.

Claim 5. (Previously Presented) The information signal transmission method according to Claim 1, wherein said second electronic device always supplies said device information over said transmission line.

Claim 6. (Previously Presented) The information signal transmission method according to Claim 1, wherein said second electronic device supplies said device information over said transmission line at intermittent time intervals.

Claim 7. (Previously Presented) The information signal transmission method according to Claim 1, wherein:

said first electronic device transmits via said transmission line a request for transmission of said device information; and

in response to said transmission request received via said transmission line, said second electronic device supplies said device information over said transmission line.

Claim 8. (Previously Presented) The information signal transmission method according to Claim 1, wherein said second electronic device supplies said device information over said transmission line such that said device information has a lower signal level than a signal level of said primary information signal.

Claim 9. (Previously Presented) The information signal transmission method according to Claim 8, wherein said second electronic device converts said device information into a signal having a low signal level by means of a spread spectrum conversion.

Claim 10. (Previously Presented) The information signal transmission method according to Claim 1, wherein when said second electronic device is supplying said device information over said transmission line, said second electronic device does not process said primary information signal received via said transmission line.

Claim 11. (Cancelled).

Claim 12. (Currently Amended) The information signal transmission method according to Claim ~~11~~ 1, wherein when said operation status information received via said transmission line indicates said second electronic device is in the recording mode and when copy management information attached to said primary information signal indicates that copying is prohibited, said first electronic device does not output said primary information signal.

Claim 13. (Currently Amended) The information signal transmission method according to Claim ~~11~~ 1, wherein when said operation status information received via said transmission line indicates said second electronic device is in the recording mode and when copy management information attached to said primary

information signal indicates only a first-generation copy is permitted, said first electronic device rewrites said copy management information to indicate copying is prohibited and outputs said primary information signal with said rewritten copy management information attached thereto.

Claim 14. (Previously Presented) The information signal transmission method according to Claim 1, wherein:

a digital serial output terminal is used in place of said analog output terminal and a digital serial input terminal is used in place of said analog input terminal; and

said first electronic device detects said device information supplied in the form of the electronic signal over said transmission line and controls the output of said primary digital data in accordance with the detected device information.

Claim 15. (Currently Amended) An information signal transmission system for transmitting a primary information signal from a first electronic device acting as a sender in the system to a second electronic device acting as a receiver in the system via a transmission line connected between an analog output terminal of said first electronic device and an analog input terminal of said second electronic device, said system being characterized in that:

said second electronic device includes device information transmitting means for supplying, in the form of an electronic signal, device information associated with said second electronic

device over said information signal transmission line; and

said first electronic device includes:

device information detecting means for detecting said device information supplied in the form of the electronic signal over said transmission line; and

control means for controlling the output of said primary information signal to said second electronic device in accordance with the device information detected by said device information detecting means, wherein

said second electronic device is a recording device for recording said primary information signal on a recording medium and includes operation status information transmitting means for transmitting operation status information indicating an operation status of said recording device,

said first electronic device includes operation status detecting means for detecting said operation status information supplied via said transmission line, whereby

said control means of said first electronic device controls outputting of said primary information signal in accordance with the operation status indicated by said operation status information detected by said operation status indicating means.

Claim 16. (Previously Presented) The information signal transmission system according to Claim 15, wherein:

said second electronic device includes connection detecting

means for detecting whether an electronic device is brought into connection with said analog input terminal; and

when said connection detecting means detects an electronic device has been brought into connection with said analog input terminal, said device information transmitting means of said second electronic device supplies said device information over said transmission line.

Claim 17. (Previously Presented) The information signal transmission system according to Claim 15, wherein:

said first electronic device includes connection detecting means for detecting whether an electronic device is brought into connection with said analog output terminal; and

when said connection detecting means detects an electronic device has been brought into connection with said analog output terminal, said device information detecting means of said first electronic device detects said device information.

Claim 18. (Previously Presented) The information signal transmission system according to Claim 15, wherein said control means of the first electronic device controls outputting of said primary information signal so that said primary information signal is output after detecting said device information supplied via said transmission line.

Claim 19. (Previously Presented) The information signal

transmission system according to Claim 15, wherein said device information transmitting means of said second electronic device always supplies said device information over said transmission line.

Claim 20. (Previously Presented) The information signal transmission system according to Claim 15, wherein said device information transmitting means of said second electronic device supplies said device information over said transmission line at intermittent time intervals.

Claim 21. (Previously Presented) The information signal transmission system according to Claim 15, wherein said first electronic device includes:

request transmitting means for supplying over said transmission line a request for transmission of said device information; and

request detecting means for detecting said transmission request transmitted via said transmission line, whereby

when said request detecting means detects said transmission request, said device information transmitting means of said second electronic device supplies said device information over said transmission line.

Claim 22. (Previously Presented) The information signal transmission system according to Claim 15, wherein said device



information transmitting means of said second electronic device supplies said device information over said transmission line such that said device information has a lower signal level than a signal level of said primary information signal.

Claim 23. (Previously Presented) The information signal transmission system according to Claim 22, wherein said device information transmitting means of said second electronic device converts said device information into a signal having a low signal level by means for performing a spread spectrum conversion.

Claim 24. (Previously Presented) The information signal transmission system according to Claim 15, wherein:

said second electronic device includes information signal processing means for processing said primary information signal supplied via said transmission line, whereby

when said device information transmitting means of said second electronic device supplies said device information over said transmission line, said information signal processing means does not process said primary information signal supplied via said transmission line.

Claim 25. (Cancelled)

Claim 26. (Currently Amended) ~~he~~ The information signal transmission system according to Claim ~~25~~ 15, wherein when said operation status detecting means detects said operation status

information indicating a transition into a recording mode and when copy management information attached to said primary information signal indicates copying is prohibited, said control means of said first electronic device controls outputting of said primary information signal such that said primary information signal is not output.

Claim 27. (Currently Amended) The information signal transmission system according to Claim 25 15, wherein when said operation status detecting means detects said operation status information indicating a transition into a recording mode and when copy management information attached to said primary information signal indicates copying is permitted only for a first generation, said control means of said first electronic device rewrites said copy management information so as to indicate copying is prohibited and outputs said primary information signal together with said rewritten copy management information attached thereto.

Claim 28. (Previously Presented) The information signal transmission system according to Claim 15, wherein a digital serial output terminal is used in place of said analog output terminal and a digital serial input terminal is used in place of said analog input terminal.

Claim 29. (Currently Amended) An information signal transmitting apparatus for transmitting a primary information

signal in a system, said information signal transmitting apparatus serving as a first electronic device acting as a sender in the system and whose analog output terminal is connected to an analog input terminal of a second electronic device acting as a receiver in the system via a transmission line so that said primary information signal is transmitted from said first electronic device to said second electronic device, said information signal transmitting apparatus comprising:

device information detecting means for detecting device information associated with said second electronic device, said device information being supplied in the form of an electronic signal from said second electronic device via the transmission line for transmitting said information signal; and

control means for controlling the output of said primary information signal to said second electronic device in accordance with the device information detected by said device information detecting means; and

operation status detecting means for detecting operation status information supplied in the form of an electronic signal from said second electronic device via said transmission line, said operation status information indicating an operation status of said second electronic device, and wherein said control means controls outputting of said primary information signal in accordance with the operation status information detected by said operation status detecting means and also in accordance with the device information

detected by said device information detecting means.

Claim 30. (Previously Presented) The information signal transmitting apparatus according to Claim 29, further comprising connection detecting means for detecting whether an electronic device is brought into connection with said analog output terminal, wherein when said connection detecting means detects that an electronic device has been brought into connection with said analog output terminal, said device information detecting means detects said device information.

Claim 31. (Previously Presented) The information signal transmitting apparatus according to Claim 29, wherein said control means controls outputting of said primary information signal so that said primary information signal is output after said device information detecting means has detected said device information.

Claim 32. (Previously Presented) The information signal transmitting apparatus according to Claim 29, further comprising request transmitting means for supplying a request for transmission of said device information over said transmission line.

Claim 33. (Previously Presented) The information signal transmitting apparatus according to Claim 29, wherein said device information detecting means detects said device information transmitted via said transmission line for transmitting said primary information signal, said device information being

transmitted after being converted to a signal having a lower signal level than a signal level of said primary information signal.

Claim 34. (Previously Presented) The information signal transmitting apparatus according to Claim 33, wherein said device information detecting means receives a spread spectrum signal produced by converting said device information into a low-level signal by spread spectrum conversion means, and said device information detecting means detects said device information by performing an inverse spread spectrum conversion upon the received spread spectrum signal.

Claim 35. (Cancelled).

Claim 36. (Currently Amended) The information signal transmitting apparatus according to Claim ~~35~~ 29, wherein when said operation status detecting means detects said operation status information indicating a transition into a recording mode and when copy management information attached to said primary information signal indicates copying is prohibited, said control means controls outputting of said primary information signal such that said primary information signal is not output.

Claim 37. (Currently Amended) The information signal transmitting apparatus according to Claim ~~35~~ 29, wherein when said operation status detecting means detects said operation status information indicating a transition into a recording mode and when

copy management information attached to said primary information signal indicates copying is permitted only for a first generation, said control means rewrites said copy management information to indicate copying is prohibited and outputs said primary information signal with said rewritten copy management information attached thereto.

Claim 38. (Previously Presented) The information signal transmitting apparatus according to Claim 29, wherein a digital serial output terminal is used in place of said analog output terminal and said information signal transmitting apparatus is connected to an electronic device having a digital serial input terminal whereby said information signal transmitting apparatus outputs primary digital data via said transmission line.

Claim 39. (Cancelled).

Claim 40. (Currently Amended) An information signal receiving apparatus for receiving a primary information signal, said information signal receiving apparatus serving as a second electronic device acting as a receiver in a system and whose analog input terminal is connected to an analog output terminal of a first electronic device acting as a sender in the system via a transmission line so that said primary information signal is transmitted from said first electronic device to said second electronic device, said information signal receiving apparatus

comprising:

device information transmitting means for supplying, in the form of an electronic signal, device information associated with said second electronic device over said information signal transmission line, wherein said information signal receiving apparatus is a recording device for recording said primary information signal on a recording medium and includes operation status information transmitting means for transmitting operation status information indicating the status of said recording device.

Claim 41. (Previously Presented) The information signal receiving apparatus according to Claim 40, further comprising connection detecting means for detecting whether an electronic device is brought into connection with said analog input terminal, wherein when said connection detecting means detects that an electronic device has been brought into connection with said analog input terminal, said device information transmitting means supplies said device information over said transmission line.

Claim 42. (Previously Presented) The information signal receiving apparatus according to Claim 40, wherein said device information transmitting means always supplies said device information over said transmission line.

Claim 43. (Previously Presented) The information signal receiving apparatus according to Claim 40, said device information

transmitting means supplies said device information over said transmission line at intermittent time intervals.

Claim 44. (Previously Presented) The information signal receiving apparatus according to Claim 40, further comprising request detecting means for detecting said transmission request transmitted from said first electronic device via said transmission line, wherein when said request detecting means detects said transmission request, said device information transmitting means supplies said device information over said transmission line.

Claim 45. (Previously Presented) The information signal receiving apparatus according to Claim 40, wherein said device information transmitting means supplies said device information over said transmission line such that said device information has a lower signal level than a signal level of said primary information signal.

Claim 46. (Previously Presented) The information signal receiving apparatus according to Claim 45, wherein said device information transmitting means converts said device information into a signal having a low signal level a spread spectrum conversion means.

Claim 47. (Previously Presented) The information signal receiving apparatus according to Claim 40, further comprising process control means for controlling a process performed upon said



primary information signal supplied via said analog input terminal, wherein said process control means controls the process such that when said device information transmitting means is supplying said device information over said transmission line, said primary information signal is not subjected to the process.

Claim 48. (Cancelled).

Claim 49. (Previously Presented) The information signal receiving apparatus according to Claim 40, wherein a digital serial input terminal is used in place of said analog input terminal and said information signal receiving apparatus is connected to an electronic device having a digital serial output terminal, whereby said information signal receiving apparatus receives primary digital data via said transmission line.

Claim 50. (Cancelled).